

1414
Product Data – Manipulators
Preston-Eastin Model MA-1212 HD

Capacity

- Weight: 250 pounds on each or either end
- Travel: 12 feet actual vertical and horizontal travel

Vertical axis

- Construction: Structural steel with continuously welded roundways
- Motor: 3/4 HP AC
- Lift speed: 40 inches per minute
- Rollers: Hardened steel on eccentric shafts
- Safety: Spring-applied locking device limits uncontrolled vertical travel

Horizontal axis

- Construction: Structural steel with continuously welded roundways
- Motor: 3/4 HP variable speed DC
- Ram speed: 3 to 90 inches per minute
- Ram speed accuracy: 2% of base speed
- Rollers: Hardened steel on eccentric shafts

Base

- Construction: Welded steel
- Bearings: Tapered-roller bearings
- Locks: Two friction locks
- Standard base plate: Sixteen 7/8 inch holes on a 22-1/8 inch bolt circle

Control

- Pendant: Remote pendant with 30-foot cable
- Optional cable lengths: Available
- Ram speed control: One-turn potentiometer
- Ram Weld/Rapid Traverse: Two position selector switch
- Ram Fwd/Off/Rev: Three position selector switch
- Ram Start/Stop: Two individual pushbuttons
- Mast Up/Off/Down: Three position selector switch
- Power: 240/480V, three phase, 60 hertz

Weight

- Manipulator: 5400 pounds
- Optional free-standing base: 1270 pounds
- Optional travel car, 20' track: 7100 pounds

Options

- Additional travel, vertical or horizontal
 - Powered travel car and track, (TCP-56 and TSP-56)
 - Free-standing, four-leg base
 - Digital LED ram speed indicator
- 