



**WELD WIRE 3 TON TURNING ROLL**

<b>SPECIFICATIONS</b>	<b>WWRD-3S DRIVE ROLL</b>
<i>Model</i>	WWRD-3S
<i>Load Capacity</i>	3,000 lbs. each
<i>Diameter Range</i>	2" to 8'
<i>Tires</i>	12" diameter with 2 1/2" surface
<i>Motor</i>	1/2 Horsepower AC
<i>Control</i>	AC Vector
<i>Gear Box</i>	Primary drive w/secondary gearboxes
<i>Foot Control</i>	On/Off
<i>Speed</i>	0 to 41 inches per minute (40:1 ) standard 0 to 82 inches per minute (20:1 ) optional, notify factory when ordering 0 to 54 inches per minute (30:1) optional, notify factory when ordering
<i>Electrical Power</i>	110 volts 60 hz
<i>Dimensions</i>	65"L X 20 1/4" W X 15" H
<i>Shipping Weight</i>	410 lbs.
	<b>WWRI-3S IDLER ROLL</b>
<i>Model</i>	WWRI-3S
<i>Load Capacity</i>	3,000 lbs. each
<i>Dimensions</i>	57 1/4" L X 20 1/4" W X 15" H
<i>Shipping Weight</i>	230 lbs.
	<b>SET TURNING CAPACITIES</b>
<i>1 Drive &amp; 1 Idler</i>	6,000 lbs. Approximately
<i>1 Drive &amp; 2 Idlers</i>	9,000 lbs. Approximately
	<b>OPTIONS</b>
<i>Foot Controls</i>	Variable speed
<i>Hand Pendant</i>	Speed control, Rapid, For/Rev, Start, Stop w/25' S/O cord

*Specifications for Weldwire idler rolls are the same as the drive rolls except that the idler roll is not power driven.*